# Hisense

# **GoBoard** Live

#### Native Apps

























### 65" ADVANCED INTERACTIVE DISPLAY

Hisense Interactive Display solutions deliver unrivalled performance and market leading value. Combining the power of a digital display, tablet, electronic whiteboard and video conference device, Hisense delivers the ultimate all-in-one display solution. Superior processors and the latest touch technology provide best-in-class user experiences while seamless wireless integration makes collaboration both simple and engaging. The NEW 65MR6DE GoBoard Live display features Google Certification, Android 13 operating system and integrated 4K camera.

#### Highlights



#### 4K Ultra HD Panel / 4K UI

The 4K Ultra HD picture quality ensures perfect colour and rich details in all possible surroundings. In addition to the 4K screen as always, we bring a 4K user interface for the GoBoard. With the 4K UI, we can use this clear and bright screen to provide the most beautiful imagery.





A built-in ambient light sensor automatically adjusts the screen brightness according to current light conditions. This display is Energy Star certified to help you protect the environment and save costs.



#### **Google Integration**

With Google Education, GoBoard enables users to easily access Google applications such as Google Classroom, Google Chrome, Play Store, Gmail, Google Drive, Google Docs, etc. This helps teachers save time managing their classroom and assignments.



#### Safer and Enhanced Experience

Android 13 works to keep your data safe and secure. With Android 13, you have more control over what information apps can and can't access. Devices that work better together, enhance your messaging, audio and multitasking experiences.



#### Smart whiteboard

GoBoard uses high-level touch to restore natural writing habits by enabling pen tip writing, cap erasing, finger moving objects and palm erasing, while also providing teachers and students with a wide range of teaching tools such as protractors, triangles and rulers.



#### **Dolby Atmos**

Integrated 4K camera

Movies, TV shows, sports, music – the entertainment you love is even better when you hear it in Dolby Atmos. Its crystal clarity, easyto-hear dialogue, great detail, and realistic surround-sound effects all come together to dial up the impact of your favourite scenes and




#### Wireless transmission

GoBoard supports Webcast, Miracast, Dongle Transfer, Hisenseshare, etc. Dual WiFi modules simultaneously support a screen-sharing hotspot and Wi-Fi network connection. With low image latency, you'll enjoy a faster, more stable connection.and a superb screen-sharing experience.



The integrated 4K GOBOARD camera is designed with a physical cover and a working light to ensure the privacy of attendees.







## Specifications

Interactive Display Panel	
LCD Size Backlight Type Resolution	
Brightness Contrast Ratio	65"
Response Time Refreshing	D-LED
Frequency Viewing Angle Lifetime	3840x2160(pixels)
Color Gamut(X% NTSC) Display	350nits
Colors	1200:1(typ.)
	8ms (typ.)
	60Hz
	178°(H) / 178°(V)
	50,000 hrs (min.)
	72%
	1.07B(10bit)

#### System

СРИ	Architecture - ARM A73(4) +A53(4) Working Frequency - 2.2GHz + 2.0GHz
GPU	MaliG52
RAM	4GB
ROM	64GB
OS	Android 13.0
Language	Chinese, English, Polish, German, French, Italian, Spanish, Finnish, Norwegian, Swedish, Thai, Indonesian, Japanese

#### Power

Power Requirements	
Power Consumption Without OPS	AC 100 V ~ 240 V, 50/60 Hz
Standby Consumption	240W (Max)
Built In Speaker	<0.5W
	2x15W+20W

#### Connectivity

OPS Power	
	DC 12V/5A IEE
Wi-Fi	802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G)
Bluetooth	BT5.1
NFC	Yes
Camera	Yes
Input	HDMI (2.0) IN x3 OPS (Optional) x1 LAN x1 (1000baseT R) USB3.0 x3 Type-C x1 (Support PD 65W) Touch x1 Audio In x1 RS-232 In x1(RJ45) RS232 OUT x2 (RJ45)
Output	HDMI Out x1 S/PDIF Out x1 Audio Out x1

#### Touch

Sensing Type	
Surface Protection	Infrared Touch Frame
Infrared Touch	Anti-Glare Glass
Touch Accuracy	≤20 points
Theory Clicks	90%(±1mm)
Minimum Touch Object	Unlimited
Writing Height	≥2mm
Windows 10/8/7,Android	<1.5mm (Support Four-Level Recognition) Multi Touch
	Width Fouch

#### Physical

Product Size (W x H x D)	1488 x 935 x 122mm 58.6 x 36.8 x 4.8 inch
Package Size (W x H x D)	1629 x 1040 X 240mm 64.1 x 40.9 x 9.4inch
Net Weight	35kg / 77.18lbs
Packed Weight	45kg / 99.23lbs
Housing Material	Front Shell: Aluminium Rear Shell: Plastic
Housing Colour	Black + Tarnish
VESA	600 x 400mm, 4-M8 Screw

#### Certification


Dimensions


Standard Certification	CB/CE/ERP/South Africa Efficiency/
	cTI IVus /CEC/ECC/ICASA/Energy Star





**65"** | 1488W x 935H x 122D mm / 58.6 x 36.8 x 4.8 inch 35 kg / 77.18 lbs





# PRODUCT CODE:IWB65DE รุ่น65MR6DE ราคา 155,000.00