Hisense

GoBoard Native Apps





75MR6DE-E 75" ADVANCED INTERACTIVE DISPLAY

Hisense Interactive Display solutions deliver unrivalled performance and market leading value. Combining the power of a digital display, tablet, electronic whiteboard and video conference device, Hisense delivers the ultimate all-in-one display solution. Superior processors and the latest touch technology provide best-in-class user experiences while seamless wireless integration makes collaboration both simple and engaging. The NEW 75MR6DE-E GoBoard display features Google Certification and Android 13 operating system.

Dual

Highlights



4K Ultra HD Panel / 4K UI

The 4K Ultra HD picture quality ensures perfect colour and rich details in all possible surroundings. In addition to the 4K screen as always, we bring a 4K user interface for the GoBoard. With the 4K UI, we can use this clear and bright screen to provide the most beautiful imagery.



Smart Power

A built-in ambient light sensor automatically adjusts the screen brightness according to current light conditions. This display is Energy Star certified to help you protect the environment and save costs.



Smart whiteboard

GoBoard uses high-level touch to restore natural writing habits by enabling pen tip writing, cap erasing, finger moving objects and palm erasing, while also providing teachers and students with a wide range of teaching tools such as protractors, triangles and rulers.



Wireless transmission

GoBoard supports Webcast, Miracast, Dongle Transfer, Hisenseshare, etc. Dual WiFi modules simultaneously support a screen-sharing hotspot and Wi-Fi network connection. With low image latency, you'll enjoy a faster, more stable connection.and a superb screen-sharing experience.





Google Integration

With Google Education, GoBoard enables users to easily access Google applications such as Google Classroom, Google Chrome, Play Store, Gmail, Google Drive, Google Docs, etc. This helps teachers save time managing their classroom and assignments.



Safer and Enhanced Experience

Android 13 works to keep your data safe and secure. With Android 13, you have more control over what information apps can and can't access. Devices that work better together, enhance your messaging, audio and multitasking experiences.



0

Dolby Atmos

Movies, TV shows, sports, music – the entertainment you love is even better when you hear it in Dolby Atmos. Its crystal clarity, easyto-hear dialogue, great detail, and realistic surround-sound effects all come together to dial up the impact of your favourite scenes and events.

Eye comfort

Certified by TÜV Rheinland, Hisense GoBoard has been proven to effectively protect your eyes by reducing the blue light ratio, even after long times looking at this screen.



Hisense

Specifications

Interactive Display Panel

LCD Size Backlight Type Resolution				
Brightness	Contra	st Ra	atio	
Response	Time	Refresh	ing	
Frequency Viewing Angle Lifetime				
Color Gam	ut(X% NT	SC) Disp	olay	
Colors				

75″
D-LED
3840x2160(pixels)
350nits
1200:1(typ.)
8ms (typ.)
60Hz
178°(H) / 178°(V)
50,000 hrs (min.)
72%
1.07B(10bit)

System

СРИ	Architecture - ARM A73(4) +A53(4) Working Frequency - 2.2GHz + 2.0GHz
GPU	MaliG52
RAM	4GB
ROM	64GB
05	Android 13.0
Language	Chinese, English, Polish, German, French, Italian, Spanish, Finnish, Norwegian, Swedish, Thai, Indonesian, Japanese

Power

Power Requirements	
Power Consumption Without OPS	AC 100 V ~ 240 V, 50/60 Hz
Standby Consumption	350W (Max)
Built In Speaker	<0.5W
	2x15W+20W

Connectivity

DC 12V/5A
IEEE 802.11a/b/g/n/ac/ax(2.4G and 5G) IEEE 802.11a/b/g/n/ac(2.4G and 5G) BT5.1
Yes
No
NU
HDMI(2.0) IN x3 OPS (Optional) x1 LAN x1 (1000baseT R) USB3.0 x3 Type-C x1 (Support PD 65W) Touch x1 Audio In x1 RS-232 In x1(RJ45)
R5232 OUT x2 (RJ45) HDMI Out x1 S/PDIF Out x1 Audio Out x1

www.genivegreen| Contact Us: ittipol.genivegreen@gmail.com 062-2942516

Touch	
Sensing Type	
Surface Protection	Infrared Touch Frame
Infrared Touch	Anti-Glare Glass
Touch Accuracy	≤20 points
Theory Clicks	90%(±1mm)
Minimum Touch Object	Unlimited
Writing Height	≥2mm
Windows 10/8/7,Android	<1.5mm (Support Four-Level Recognition)

Multi Touch

Physical

Product Size (W x H x D)	1709.9 x 1024.4 x 118.8mm 67.3 x 40.3 x 4.7 inch
Package Size (W x H x D)	1850 x 1165 x 240mm 72.8 x 45.9 x 9.4 inch
Net Weight	45.5kg / 100.3 lbs
Packed Weight	59.7kg / 131.6 lbs
Housing Material	Front Shell: Aluminium Rear Shell: Plastic
Housing Colour	Black + Tarnish
VESA	600 x 600mm, 4-M8 Screw


Certification

Standard Certification

CB/CE/ERP/South Africa Efficiency/ cTUVus/CEC/FCC/ICASA/Energy Star

Dimensions

75" 1710W x 1025.5H x 126D mm / 67.3 x 40.4 x 5 inch 45.3 kg / 99.89 lbs



genive green Co.,Ltd. บริษัท เจนิเว่ กรีน จำกัด

PRODUCT CODE:IWB75DE-E รุ่น 75MR61DE-E ราคา 197,950.00